

Paving the Way for Enriched Metadata of Linguistic Linked Data

Maria Pia di Buono ^{a,*}, Hugo Gonalo Oliveira ^b, Verginica Barbu Mititelu ^c, Blerina Spahiu ^d,
Gennaro Nolano ^a

^a *UniOr NLP Research Group, Departments of Literary, Linguistics and Comparative Studies, "L'Orientale"
University of Naples, Italy*

E-mail: {mpdibuono,gnolano}@unior.it

^b *CISUC, Department of Informatics Engineering, University of Coimbra, Coimbra, Portugal*

E-mail: {hroliv}@dei.uc.pt

^c *Romanian Academy Research Institute for Artificial Intelligence, Bucharest, Romania*

E-mail: {vergi}@racai.ro

^d *Department of Informatics, Systems and Communication, University of Milano-Bicocca, Milano, Italy*

E-mail: {spahiu}@unimib.it

Abstract. The need for reusable, interoperable, and interlinked linguistic resources in Natural Language Processing downstream tasks has been proved by the increasing efforts to develop standards and metadata suitable to represent several layers of information. Nevertheless, despite those efforts, the achievement of full compatibility for metadata in linguistic resource production is still far from being reached. On the other hand, access to resources observing these standards is hindered either by (i) lack of or incomplete information, (ii) inconsistent ways of coding their metadata, and (iii) lack of maintenance. In this paper, we offer a quantitative and qualitative analysis of descriptive metadata and resources availability of two main metadata repositories: LOD Cloud and Annohub. Furthermore, we introduce a metadata enrichment, which aims at improving resource information, and a metadata alignment to a descriptive schema, suitable for easing the accessibility and interoperability of such resources.

Keywords: Linguistic Linked Open Data, Metadata enrichment, Meta-Share, Annohub, LOD Cloud

1. Introduction

The need for reusable, interoperable and interlinked linguistic resources (LRs) in Natural Language Processing (NLP) downstream tasks has been proved by the increasing efforts to develop standards and metadata suitable to represent several layers of information. Nevertheless, despite those efforts, the achievement of a full compatibility for metadata in linguistic resource production is still far from being reached [1].

To overcome this limitation and to support a metadata harmonization process, several initiatives (e.g.,

LRE map¹, European Language Grid², CLARIN³, Nexus Linguarum⁴, Prêt-à-LLOD⁵, Elexis⁶) have been proposed to promote community-based documentation and definitions of existing resources and standards. However, many challenges about resource discovery, reuse and integration are still present, due to the fact that issues of interoperability between different types of resources persist [2].

Lately, as ontology-based approaches have become a wide-spread method for modelling linguistic data,

¹<https://lremap.elra.info/>

²<https://www.european-language-grid.eu/>

³<https://www.clarin.eu/>

⁴<https://nexuslinguarum.eu/>

⁵<https://pret-a-llod.github.io/>

⁶<https://elexis.is/>

*Corresponding author. E-mail: mpdibuono@unior.it

mainly on the Semantic Web [3], several linguistic resources have been developed, in compliance with Linked Data (LD) principles⁷ and the number of datasets published as LD resources has increased at quite a fast pace (see Section 3).

Under the LD paradigm, data should comply to the aforementioned principles to ensure an easy discoverability, as well as an easy way to query information within the data [4]. The adoption of LD best practices assures that the structure and the semantics of the data are made explicit, which is also the main goal of the Semantic Web.

Nevertheless, descriptive metadata useful for retrieving and accessing such LD resources are still far away from being fully informative and interoperable, as they are not always up-to-date, shared and harmonized among providers and among repositories. Indeed, metadata used for describing an LD resource may be different, depending on the description schema applied and on the information provided by owners/creators as well as by repository maintainers. The heterogeneous nature of data sources may cause inconsistent as well as misinterpreted and incomplete metadata information [5].

Moreover, resources can become unavailable over time, as their landing pages or endpoints may change or be not accessible anymore. For example, within one of the main metadata repositories, i.e., LOD Cloud⁸, sentiws⁹ a German-language resource for sentiment analysis, opinion mining is not available, neither the dump nor the endpoint even though the information that points to the dump¹⁰ and to the SPARQL endpoint¹¹ does exist¹².

Thus, even though LD datasets are considered to be a gold mine as they can ease the access and interlink with other valuable interoperable resources, their usage is still limited, as finding useful datasets without prior knowledge is getting more complicated. In fact, in order to decide if the dataset is useful or not, one should have access to its descriptive metadata, where information about the content, such as its domain, ac-

cess point, data dump or SPARQL endpoint, release and update dates, license information, etc., should be available. However, metadata do not always provide all this information, but they become fundamental for a first skimming. Dataset usage becomes even more challenging when the dataset does not come with metadata information at all, or when such information is partially missing. Access to reliable metadata is important for different use cases such as: they provide a landscape view, help with the dataset and ontology integration, and help with the data analysis.

Starting from these observations, we present a quantitative and qualitative analysis of the descriptive metadata and the resources availability from two main metadata repositories: Linked Open Data (LOD) Cloud and the Annotation Hub (Annohub)¹³. Furthermore, we introduce a metadata enrichment effort, which aims at improving resource information, and a metadata alignment to a descriptive schema, in compliance with a minimal level of description suitable for easing the accessibility and interoperability of such resources (see Section 4).

With respect to the state-of-the-art, we make the following contributions:

- provide an analysis of the current status of linguistics resources: the domain that the resource belongs to, its language, type and license. Such analysis provides a general overview of the status of LOD and Annohub datasets.
- propose metadata alignment to a shared metadata model to harmonize the information within different repositories;
- propose metadata enrichment for the existing information;
- evaluate the accessibility/availability of existing linguistic LD resources.

The remainder of this paper is organized as follows: Section 2 describes related work with reference to four lines of research, i.e., linguistic data cataloguing, quality evaluation, data enrichment, and metadata modeling. Following this, Section 3 presents the two main sources for LD and Section 4 introduces the methodology applied for both the metadata alignment and enrichment tasks. In Section 5 we provide a resource and metadata analysis from two main perspectives, domains and languages covered, with the purpose of highlighting the effort of enriching the meta-

⁷https://en.wikipedia.org/wiki/Linked_data#Principles

⁸<https://lod-cloud.net>

⁹<https://lod-cloud.net/dataset/sentiws>

¹⁰<https://wortschatz.informatik.uni-leipzig.de/download/>

SentiWS_v1.8c.zip

¹¹<http://mlode.nlp2rdf.org/sparql>

¹²It is worth mentioning that the LOD Cloud reports resource unavailability by means of an alert signal. However, we found examples where, despite the alert, we could download the dataset, as well as the opposite.

¹³<https://annohub.linguistik.de>

data. In Section 6 special attention is paid to linguistic resources, to the status of various languages in these repositories (i.e., low- or high-resourced), to their availability for interested parties, as well as to the type of license under which they are released. Finally, in Section 7 we present the conclusions and future work.

2. Background

In the recent years, many efforts have been made in order to link together the ever growing number of linguistic resources available on the Web. The literature on the topic mainly focuses on the following lines of research: *linguistic data cataloguing*, *quality evaluation*, *data enrichment* and *metadata modeling*.

Linguistic Data Cataloguing: Cataloguing linguistic LD calls for huge efforts, as often the field of domain in datasets' description is used ambiguously [6, 7].

In this regard, in Chiarcos et al. [2] LOD principles are applied to linguistic data, with the aim to produce a web application to make such data querable, interoperable and easy to share and expand through the Web. The result is the *Linguistic Linked Open Data Cloud*¹⁴ (LLOD Cloud).

As an attempt to tackle two of the main shortfalls of the LLOD Cloud (i.e., the variations of language encoding standards and the lack of common metadata schemas for LD), Abromeit et al. [8] proposes *Annohub*, a dataset composed of languages and annotation schemes already used in language resources. In particular, the schemes are supported by and linked to the thesaurus of the Bibliography of Linguistic Literature¹⁵ (BLL).

Still, a high degree of heterogeneity in terms of representation formats is present among linguistic resources. An attempt to model linguistic LD datasets is the one by Bosque et al. [9], in which models are described according to how the linguistic knowledge is represented and to the granularity of the information they provide.

Quality Evaluation: The evaluation of quality issues related to cataloguing LD has represented an important topic of discussion in recent years. Research by Hainain et al. [10] shows, for example, that, when working with data from the LOD Cloud through CKAN Datahub¹⁶, a tool helping to manage and publish col-

lections of data, several issues may arise, especially in relation to ease of access to data. In particular: ownership related information was missing 41% of the cases, 64% of the general metadata (e.g., `size` and `url_type` values) and 80% of the provenance information contained missing values. Furthermore, many datasets contain unreachable/undefined URLs and inconsistent values in data fields.

Debattista et al. [11] performs a quality evaluation of several datasets from the LOD Cloud as a way to ease the search and processing of LD. The authors use the Dataset Quality Vocabulary [12] as a semantic quality metadata graph to make it possible for users to search, filter and rank datasets according to some quality criteria. The metrics used in this work, described by Zaveri et al. [13], deal with the assessment of data quality with regards to the following categories, each with its own set of quality dimensions:

- Accessibility Dimensions (availability, licensing, interlinking, security and performance);
- Intrinsic Dimensions (syntactic validity, semantic accuracy, consistency, conciseness and completeness);
- Contextual Dimensions (relevancy, trustworthiness, understandability and timeliness);
- Representational Dimensions (representational-conciseness, interoperability, interpretability and versatility).

Through the use of Principal Component Analysis (PCA), Debattista et al. [11] shows that only 3 out of 27 metrics could be regarded as non-informative to the final quality assessment of data. Overall, the results show that some improvements are needed when handling this kind of data. The score for each quality metric was aggregated to a conformance score that was shown to be slightly below 60%, with a number of problems related to LD publishing and conformance to best practices/guidelines.

The non-conformance to LOD guidelines is proven to be a problem in data quality and, as this is particularly common, especially in regards to certain pieces of information (e.g. Licensing and Human-Readable Metadata) [14].

Data Enrichment: One further topic of discussion tackles the need to solve the sparsity of information in LOD resources through data enrichment. Ding and Finin [15] shows that, despite the ever growing size of the Semantic Web, the majority of metadata such as `rdfs:comment`, `rdfs:label`, `dc:title`, etc., is never used in the data. Similarly, the results

¹⁴<http://linguistic-lod.org/lld-cloud>

¹⁵<https://data.linguistik.de/bll/index.html>

¹⁶<https://ckan.org/datahub/>

of the cataloguing of Life Science Linked Open Data (LSLOD) [10] show that, for most datasets, there is little to no reuse of both ontologies and URIs. They use unpublished schemes resulting in high semantic heterogeneity [16]. These issues clearly pose serious problems in the attempts to align resources, which, even when dealing with a single domain, needs to be solved through an enrichment of the data. Paulheim [17] describes three main axes to classify data refinement when dealing with concepts:

- completion (i.e., adding missing knowledge) vs error detection (i.e., the identification of wrong information);
- target of refinement;
- internal approach (i.e., using just the knowledge at hand) vs. external approach (i.e., making use of external human knowledge).

However the attempts, none of the approaches was able to correct and complete knowledge at the same time. In particular, the absence of approaches that are able to find and correct errors is highlighted. Furthermore, it is shown that most approaches focus on only one target (e.g. relations, literals, etc.).

Metadata Modeling: The efforts of cataloguing several different datasets show the need for a uniform metadata model to improve the interoperability of data and facilitate retrieval processes and reuses of resources. One such model was proposed by Gavriliadou et al. [18] as the core engine for the META-SHARE infrastructure¹⁷ for the sharing of Language Resources (LRs). The basic needs answered by this model are:

- to identify and model all types of LRs and the relations occurring between them;
- to apply for a common terminology;
- to use minimal schemas that nevertheless allow for exhaustive descriptions;
- to guarantee interoperability between LRs, tools and repositories.

The principles at the core of META-SHARE designed to tackle these needs are described as:

- expressiveness of LR typology in order to cover any type of resource;
- extensibility of the schemes through their modularity;

¹⁷<http://www.meta-share.org/>

- semantic clarity of each element of the schema, which is thoroughly described;
- flexibility through the definition of a two tier schema which allow for different levels of description;
- interoperability through the mappings to popular schemes (mainly Dublin Core).

One of the main topics of discussion in the META-SHARE model is in the typology of resources, with two different values to classify LRs: `resourceType` and `mediaType`. The axis `mediaType` deals with the medium (or media) used in the LR, and the authors suggest as possible values: text, audio, image, video, or a combination of these.

`ResourceType`, on the other hand, describes features specific to each possible typology of LR. In particular, the authors suggest for this element: corpus, lexical/conceptual resource, language description, and tool/service.

In this model, the classification of LRs is also helped by the use of metadata elements (e.g., the value for `lingualityType` can be used as a means to distinguish between mono-, bi- and multilingual resources). The schema¹⁸ for the META-SHARE model can describe LRs across several dimensions (see Section 4).

3. Repositories

As previously stated, our survey, conducted within the framework of Nexus Linguarum CA 18209, is based on the information about resources in linked data formats available from two sources: the LOD Cloud and Annohub.

Neither of them is a place for storing resources, as they are both repositories of the metadata that describe such resources. Each repository has its own characteristics, making them suitable for contributing to our analysis of the state-of-the-art in LOD accessibility, interoperability and re-use, and to the development of a new resource based on a uniform metadata model.

3.1. LOD Cloud

The LOD Cloud is a diagram that offers an up-to-date image of the freely available linked datasets

¹⁸The full documentation for Language Resources in the META-SHARE model can be found at https://european-language-grid.readthedocs.io/en/release1.0.0/Documentation/ELG-SHARE_xsd_Element_ms_LanguageResource.html

in various domains, maintained by the Insight Centre for Data Analytics¹⁹. The diagram uses different colours to render the datasets pertaining to nine domains (see Table 1), including a pool of cross-domain datasets. For every dataset in the cloud, the topic is either assigned by verifying its content or by accessing the metadata assigned by the publisher [7]. With 12 datasets in 2007, the LOD Cloud has grown constantly since then. In 2014, the Web was crawled by the LD Spider framework [19], which follows dataset interlinks.

The crawler seeds originate from three sources: (i) datasets from the *LOD Cloud* in `datahub.io` datasets catalog, as well as other datasets marked with Linked Data related tags within the same catalog; (ii) a sample from the *Billion Triple Challenge* 2012 dataset²⁰; and (iii) datasets advertised since 2011 in the mailing list of `public-lodw3.org`. Since 2014 more frequent releases of the LOD Cloud have taken place. The cloud contains 1,440 datasets as of 20-05-2020.

As mentioned before, the LLOD cloud [2] was established in 2011 as a means “to measure and visualize the adoption of linked and open data within the linguistics community” [20]. It is the result of an effort by the Open Linguistics Working Group²¹ and contains two kinds of resources: linguistic resources in a strict sense (e.g., dictionaries, wordnets, annotated corpora such as treebanks) and other linguistically-relevant resources (e.g., thesauri from tourism or life sciences, such as EARTH – the Environmental Applications Reference Thesaurus [21]); all of which are linguistically-relevant resources, and various downstream tasks can make use of them in data processing.

The diagram representing the LLOD Cloud is generated from the metadata in LingHub²² [22], which is an indexing and search service that does not store metadata or resources, but provides harmonization of the metadata in different formats.

Although envisaged to reflect the linguistically-relevant resources available as linked data and with an open license, this is not fully observed at the moment (see also Section 6.2). McCrae et al. [20] write about a validation step when including resources in the LLOD Cloud. A new resource is included if: (i) its meta-

data contain a link to a resource already in the LLOD Cloud, and (ii) the resource is available for download.

The evolution of the number of resources in the cloud, presented by Chiarcos et al. [23], reveals a 19.3% increase every year since its establishment. The LLOD Cloud considered for this survey contains 136 resources²³.

3.2. Annohub

Annohub [8] refers to both a software and a repository: the former queries various sources (including, e.g., LingHub, CLARIN and individual resources providers) of metadata of linguistic resources, while the latter stores the collected metadata. Annohub also comes with tools for language and annotation model detection. At the moment, the Annohub repository contains 604 resources with associated metadata, automatically enriched with information about the language and the annotation model used. For the purpose of this paper, we count Universal Dependencies treebanks only once irrespective of the fact that they are listed twice in the dump file because they are available in two formats (i.e., RDF²⁴ and CONLL-U²⁵); the remaining number of resources considered in this paper is 530. The main reason for choosing these repositories relies in the type of information they encompass. The LOD Cloud collects metadata for several resources on different domains, while Annohub contains only metadata about annotated linguistic resources from reliable sources.

4. Methodology

The aforementioned metadata repositories have been developed for different aims and by means of different approaches, and so, they apply two different metadata schemes to collect information. This means that we would have different metadata information also for the overlapping resources, i.e., according to our analysis there exist 69 overlapping datasets (see Section 5).

In fact, the LOD Cloud and Annohub collect different types of metadata with different levels of gran-

¹⁹<https://www.insight-centre.org/>

²⁰<http://km.aifb.kit.edu/projects/btc-2012/>

²¹<http://linguistics.okfn.org/>

²²<http://linghub.org>

²³There are only 133 resources with this domain assigned in the metadata, but we were able to assigned other three resources to linguistics domain during the metadata enrichment phase.

²⁴<https://www.w3.org/RDF/>

²⁵<https://universaldependencies.org/format.html>

ularity. Besides the differences noted in the metadata schemes, these two repositories apply two different approaches to the recollection of resource information. Metadata information from the LOD Cloud is provided by the different resource providers/developers, while metadata information from Annohub are automatically generated from CLARIN, LingHub [22] resource metadata, or other reliable resource providers [8] so that they can be consistent and coherent.

Due to the fact that the LOD Cloud uses a bottom-up approach to collect the provided information, some metadata information may be missing (e.g., for some of the Universal Dependencies²⁶ [24] treebanks, such as the Indonesian and the Czech ones, the language is not specified), or inconsistent, e.g., different names are used to refer to the same content. For instance, to indicate the language for resources on modern Greek, either *Modern Greek (1453-)* or simply *Greek* are used.

Furthermore, there also exist some inconsistencies within the LOD metadata themselves, e.g., *linguistic* and *linguistics* are used interchangeably to refer to resources belonging to the linguistic domain. The presence of this kind of inconsistencies would make it difficult for the potential user to retrieve all the resources from the respective domain when searching only for one of the two forms, in this case most probably the noun, i.e. *linguistics*, and would limit resource inter-linking as well.

To harmonize and enrich the existing metadata, we adopt a two-step procedure, as follows:

1. Metadata alignment/mapping;
2. Metadata enrichment.

Before moving to these two steps, we extract the information from both repositories by means of the dumped files, as they have been first organized according to their specific metadata schema. Then, we fix the inconsistencies among the values for several fields, e.g., domain, language, license type, and proceed aligning such information to a new metadata schema, based on META-SHARE classes and properties, identified as core information with regards to usability and accessibility principles and considered useful for quality evaluation of both metadata and resources themselves. Finally, enrichment has been performed both automatically and manually with the aim of providing consistent values for the new metadata model.

²⁶universaldependencies.org

4.1. Metadata Alignment/Mapping

The alignment of the existing metadata to the set of META-SHARE properties and classes has been performed starting from the analysis of the differences between the two metadata schemes. For instance, while the LOD Cloud has a field to indicate the *domain* and another one to specify *keywords* about the resources, the Annohub repository uses a *description* field to aggregate different information, e.g., models, annotation types. As far as the LOD Cloud metadata schema is concerned, a number of fields about available endpoints and downloads (e.g., SPARQL status, SPARQL link, Full download) and about provider/contact information (e.g., Owner, Contact point, Contact point email) are provided. On the other hand, Annohub metadata offer the possibility to include more fine-grained description about types, formats, languages and copyright information. In compliance with the LD principles for resource metadata, we select a set of properties and classes among the ones proposed by the META-SHARE ontology, grouped according to the criterion they satisfy, as follows²⁷:

– Classification:

- * `metadataRecordIdentifier` a string (e.g., PID, DOI, internal to an organization, etc.) used to uniquely identify a metadata record;
- * `resourceName` to introduce a human-readable name or title by which the resource is known;
- * `resourceCreator` links a resource to the person, group or organisation that has created the resource;
- * `ORCID Open Researcher and Contributor Identifier`;
- * `languageVariety` A particular linguistic system used in a specific region or by a social group;
- * `domain/categoryLabel` to introduce a human readable name (label) by which a classification category (e.g. text type, text genre, domain, etc.) is known;
- * `LCRsubclass` to classify of lexical/conceptual resources into types (used for descriptive reasons);

²⁷For the sake of this paper, we analyse deeply only some of the META-SHARE classes and properties in our enriched metadata resource. See Section 5 and Section 6.

- * `subject` to classify a situation, event, thing, etc. that is discussed in the contents of a language resource;
 - * `ontology` to report the format for the ontology used in developing the resource;
 - * `externalReference` to provide reference to another resource to which the lexicalConceptualResource is linked (e.g., link to a word-net or ontology);
 - * `size/amount` with reference to the number of triples. This value might be used for indirect assessment of quality as we assume that a low number of triples indicates that the resource is poor.
- Usability:
- * `generalDocumentation` used for documents that describe a language resource or some aspect of it;
 - * `landingPage` links to a web page that provides additional information about a language resource (e.g., its contents, acknowledgements, link to the access location, etc.);
 - * `licence` to allow the linking to a licence with a specific condition/term of use imposed for accessing a language resource. META-SHARE considers this as an optional element and only to be considered to provide brief human readable information on the fact that the language resource is provided under a specific set of conditions.
 - * `dataFormat` to indicate the format(s) of a data resource; `description` to report a short free-text account that provides information about the resource (e.g., function, contents, technical information, etc.);
 - * `contact/email` to report the data of the person/organization/group that can be contacted for information about a resource.
- Accessibility:
- * `downloadLocation` A URL to the resource download page;
 - * `accessLocation` A URL to the SPARQL endpoint;
 - * `externalResource` to specify the formalism (bibliographic reference, URL, name) used for the creation/enrichment of the resource.
- Quality:

- * `Validation` to specify whether the resource has undergone a formal validation process with reference to accessibility parameters/classes;
- * `annotationSchema` to refer to the vocabulary/standard/best practice to which a resource is compliant with. It allows links to the standard/model used for the creation of the resource;
- * `distributionLocation/comment` and `accessibleThroughQuery/comment` to indicate if the respective URLs are working/broken or a demo;
- * `accessibleThroughQuery` value for dataset distribution medium, used for lexical/conceptual resources that can be accessed via a SPARQL endpoint;
- * `externalResource/comment` to validate the link to the ontology used as formalism.

Furthermore, the classification of LR is helped by the use of metadata elements (e.g., the value for *lingualityType* can be used as a means to distinguish between mono-, bi- and multilingual resources). To merge the existing metadata, we apply an alignment procedure between the information available in both repositories and the new metadata schema based on META-SHARE properties and classes.

4.2. Metadata Enrichment

Finally, we proceed with a metadata enrichment phase, which has been achieved both automatically and manually.

The automatic extraction procedure focuses on fields that encompass different types of information: language, domain, type, the values of names, labels, and keywords. For instance, from the names of the UD treebanks we could easily extract information about their language and infer that, being a treebank, they are of type *corpora*. Such information might be inferred even for those resources lacking this information in the metadata, as in the case of the Indonesian and Czech ones within the LOD Cloud (see Section 3 and Section 6). In addition to this, in some cases, when available, the resources content has also been considered, especially its textual properties. For example, in Annohub, the description field may present more fine-grained information related to a resource, so that the enrichment of additional metadata results quite straightforwardly. For instance, considering the following example of a resource description

from Annohub, we could infer information about the annotation types and schemes (reported in bold face):

*Universal Dependencies is a project that seeks to develop cross-linguistically consistent **treebank annotation** for many languages, with the goal of facilitating multilingual parser development, cross-lingual learning, and parsing research from a language typology perspective. The annotation scheme is based on (universal) **Stanford dependencies** (de Marneffe et al., 2006, 2008, 2014), **Google universal part-of-speech tags** (Petrov et al., 2012), and the **Intersect** interlingua for morphosyntactic tagsets (Zeman, 2008). This dataset refers to UD's Ancient_Greek treebank.*

Then, a manual enrichment has been performed by three experts who filled in the information still missing after the automatic enrichment, so that language and domain values have been assigned to all the resources, including non-linguistic ones, while type has been assigned to linguistic resources only (see Section 6).

On the basis of such a process of alignment and enrichment (see Section 5 and Section 6 for a comparison between original and enriched information), we propose a new coherent and consistent metadata resource, aligned with a set of META-SHARE properties and classes, which encompasses enriched meta-data from both repositories²⁸.

5. Metadata Overview

The LOD Cloud includes 1,440 datasets, but, as mentioned already, its metadata is incomplete: it does not cover resource language and not all datasets have a domain assigned. On the other hand, Annohub covers 530 resources, all with an assigned language and all from the domain of linguistics. A total of 69 resources is present in both LOD Cloud and Annohub, which results in 1,908 distinct datasets considered.

Our analysis firstly focused on the domains and languages covered by the linked resources. Here, we look at the covered domains and the number of datasets for each, considering only the metadata from the LOD cloud and from Annohub (Original), then using our enriched metadata (Enriched). Following the same

²⁸The metadata resource will be made available after the review process ends.

methodology, we make a first analysis of the languages covered by the considered datasets.

5.1. CategoryLabel

Table 1 enumerates the domains covered by the LOD Cloud and the number of datasets per domain, in the original LOD metadata and in our enriched version. Whenever this field was empty, we tried to fill it in automatically or, when this was not possible, manually (see Section 4.2). Spahiu et al. [7] discuss the attempts to automatically classify datasets in the LOD into one or more domains. Even though sometimes datasets are considered as borderline between two or more domains, in this paper we assume that each dataset belongs to a single domain. Even if, in some cases, this decision was not easy (e.g., linguistic resources, like corpora or thesauri, for a specific domain, such as *GeoWordNet*²⁹ [25]), we leave further refinements of this classification, including a review of the available domains, for future work.

Table 1

Number of datasets for each domain in the LOD metadata (Original) and in the enriched metadata.

Domain	LOD	Annohub	Enriched
Life Sciences	342	N/A	343 (+1)
Government	200	N/A	223 (+23)
Publications	150	N/A	135 (-15)
Linguistics	133	530	666 (+72)*
Cross Domain	76	N/A	85 (+9)
User Generated	67	N/A	67 (=)
Social Networking	53	N/A	54 (+1)
Geography	49	N/A	53 (+4)
Media	34	N/A	38 (+4)
Metadata	N/A	N/A	14 (+14)
Education	N/A	N/A	6 (+6)
Art	N/A	N/A	4 (+4)
Tourism	N/A	N/A	2 (+2)
Other	N/A	N/A	7 (+7)
Total w/ domain	1,104	530	1,696 (+131)*

LOD datasets span through nine domains with the most represented being Life Sciences. This covers the knowledge-rich biomedical domain, which has adopted Linked Data technologies, e.g., for representing medical ontologies, such as the *Human Disease Ontology* [26], or biology ontologies, such as the *Plant Ontology* [27]. In fact, a great contribution comes from

²⁹<https://old.datahub.io/dataset/geowordnet>

the BioPortal³⁰ repository, where 244 datasets in the LOD Cloud are also indexed.

The second most represented domain is Government and the third is Publications. The former covers mainly Linked Data published by federal or local governments, including several statistical datasets. Examples in this category include the data.gov.uk [28] and opendatacommunities.org datasets. The latter holds library datasets, information about scientific publications and conferences, reading lists from universities, and citation database. Prominent datasets in this category include *German National Library* dataset, the *L3S DBLP dataset* and the *Open Library* dataset.

As far as this latter domain, Publications, is concerned, it is the only one for which the number of assigned resources has decreased in the enriched version, as a result of the fact that for a pool of resources we could assign a more appropriate domain, as well as of the fact that we considered that publications is hardly a domain [6]. Some examples of resources for which the domain field was changed from Publications to another value are: *Project Gutenberg*³¹, which was assigned the domain label `cross_domain`, already existing in the LOD Cloud; *Linked Data from the Open University*³², for which we assigned a new domain, namely education; *data-szepmuveszeti-hu*³³, assigned to the new domain art; *Santillana Guide Dataset*³⁴, assigned to the new domain tourism; or *datos.bne.es*, assigned to the new domain metadata. In Table 1 we included the nine LOD Cloud domains and the newly assigned domains.

The linguistics domain comes only in fourth place and will be further analysed in Section 6. The quantity of datasets to which this domain was assigned is presented with an asterisk (*) because, as above, there are 69 datasets in both LOD Cloud and Annohub. So, this number cannot be obtained simply by subtracting the total of linguistics datasets in both repositories to the number of datasets belonging to this domain in the enriched data.

The re-evaluation of the `categoryLabel` field is still in progress, and we expect to obtain more diverse, specific and reliable results.

5.2. Language

In this section we focus on the language metadata field of all resources, irrespective of the domain they belong to, while the next section contains the discussion of this field only for the resources in the linguistic domain.

At this level we noticed inconsistency among various resources. On one hand, there are cases when the language(s) of a resource is/are clearly mentioned in the metadata, while for others this information is missing. On the other hand, in the case of resources containing data in several languages, two ways of registering this are manifest: either the languages are enumerated (e.g., English, German, French, Spanish for *JEL Classification*³⁵) and they can sometimes be even in a high number (e.g., 262 languages are enumerated for *lemon-UBY OmegaWiki English*³⁶); or, instead, the label “multilingual” is used, but this is opaque as to the number of languages represented within the respective resource (see e.g., the resources *BabelNet* [29], *Semantic Quran* [30] or *Open WordNet (as part of Open Multilingual WordNet)* [31]).

Another type of inconsistency happens for some languages which can be referred to by means of different labels: e.g., the case of Modern Greek explained in Section 4). Another example is that of Norwegian, for which, in the case of some resources we know the variety (Bokmål or Nynorsk) as it is made explicit in the resource name (e.g., *Apertium Dictionary Danish-Norwegian.Bokmål*³⁷), but in the case of other resources only *Norwegian* is mentioned and it remains unclear if both varieties of the language are represented or only one (e.g. *Freedict RDF dictionary Finnish-Norwegian*³⁸). With the help of a native speaker, the Greek resources are now assigned the right information: either *Ancient Greek (to 1453)* or *Modern Greek (1453-)*.

For the resources lacking information about the language, effort has been invested in filling this in and, as Tables 2 and 3 show, the metadata of many resources benefited from it. More precisely, while in the original metadata, only the 530 resources in Annohub had a language assigned, in the enriched metadata, we could

³⁰<http://biportal.bioontology.org/>

³¹<http://www.gutenberg.org/>

³²data.open.ac.uk

³³<https://www.szepmuveszeti.hu/>

³⁴<http://webenemasuno.linkeddata.es/>

³⁵https://zbw.eu/beta/external_identifiers/jel/about.en.html

³⁶https://www.lemon-model.net/lexica/uby/ow_eng/

³⁷<https://github.com/acoli-repo/acoli-dicts/tree/master/stable/apertium/apertium-rdf-2019-02-03>

³⁸<https://github.com/acoli-repo/acoli-dicts/tree/master/stable/freedict/freedict-rdf-2019-02-05>

assign the language to 731 more resources, making a total of 1,261 resources with language (66%), out of which 666 are from the linguistics domain (100% for this domain). Table 2 shows the top-10 most represented languages in datasets indexed by the LOD Cloud and Annohub.

For some multilingual resources we could find a list of all the covered languages, either in the resource description or in a paper describing the resource. All the languages were added to the language field, split by commas, in a similar way to resources that already had several languages enumerated. Otherwise, if the resource was presented as multilingual and we could not find a list of the languages, we simply assigned it the label *multilingual*: this was the case for 4.4% of the resources.

We found a total of 2,768 distinct values for the language field. As expected, English is the most represented language, by a far margin. Yet, out of the English resources, almost three quarters belong to non-linguistic domains, which becomes clearer if we contrast these figures with Table 3, focused on the linguistics domain. This does not happen for most of the other languages and is explained by the fact that, in the manual assignment of languages, we considered the values of resource textual properties, namely names, labels, comments, or descriptions. It turns out that many datasets use English for labelling and commenting on their contents.

Table 2

Ten most represented languages and number of datasets covering each. Given the multilingual resources, the total number of resources is different from the sum of resources per language.

Language	LOD	AnnoHub	Enriched
English	N/A	99	577
Swedish	N/A	278	288
Spanish	N/A	50	105
German	N/A	56	86
French	N/A	56	80
Italian	N/A	45	80
Czech	N/A	28	69
Portuguese	N/A	41	52
Polish	N/A	44	50
Dutch	N/A	38	48
Total w/ language	N/A	530	1,261 (+731)

6. Focusing on the Linguistics Domain

This section presents the status of the metadata resources in the linguistics domain. The important as-

pects are: (i) the language for which they were created, as this offers insights into the efforts made for ensuring a language presence in the electronic medium, on the one hand, and in the LD landscape, on the other hand, although we do not assume a direct correlation between these two aspects; (ii) the type of information they contain and the way in which this is annotated (when applicable), so in one word, the type of the resource, (iii) the licence with which they are released to the community, and (iv) the actual availability of the resource for those interested, which is scrutinized here from two perspectives: the possibility to download their data dump and/or to query them through a SPARQL endpoint.

6.1. Linguistic LD Languages

When considering only the linguistics domain, the number of distinct languages is 2,766. Comparing it with the number of languages for which linked resources are indexed by the two repositories (see Section 5.2), we notice that there are only two languages, better, values in this field, for which LD resources exist but they either lack a domain or it is not linguistics. After inspecting these situations, we noted that they were: Bantu, which is actually a family of languages; and Swahili, for which there exist linguistics resources, but either marked as *Swahili (individual language)* or *Swahili (macro language)*. Since we do not know where the latter would fit, we left it as *Swahili* only.

Table 3 shows the languages for which there are over 30 resources in the linguistics domain. It may come as a surprise that, considering only the linguistic domain, Swedish is the highest-resourced language, but this is justified by the fact that the second major source of resources for the Annohub repository is Sprakbanken³⁹.

When comparing the ranks of languages in Table 2 and in Table 3 we notice that, in general, most of the LD resources are in the linguistics domain, with English⁴⁰ (see also the discussion about multilingual resources in Section 5) and Czech⁴¹ being exceptions⁴².

Apart from Swedish and English, no other language has more than 100 linguistics datasets. Six languages

³⁹<https://spraakbanken.gu.se/en>

⁴⁰The largest set of English resources (i.e., 274) belong to the Life Sciences domain, and linguistics comes second.

⁴¹There are 32 resources from the Government domain for Czech.

⁴²Spanish is another language for which 37% of the resources are not in the linguistics domain.

Table 3

Languages covered by 30 or more datasets in the linguistics domain and their quantity in Annohub and in the enriched metadata.

Language	AnnoHub	Enriched
Swedish	277	283
English	99	146
Spanish	50	66
German	56	66
French	56	66
Italian	45	54
Portuguese	41	48
Polish	44	47
Dutch	38	43
Catalan	34	43
Finnish	38	42
Russian	36	38
Japanese	34	38
Bulgarian	30	33
Esperanto	28	33
Modern Greek	29	36
Turkish	32	33
Latin	31	31
Romanian	27	31
Galician	26	31
Czech	28	30
Danish	28	30
Total w/ language	530	666 (+72)*

have more than 50 linguistics datasets (Spanish, German, French and Italian). Interestingly enough, there are 382 languages with at least 10 linguistic datasets.

6.2. License

The different types of licenses of the linguistic resources are presented in Table 4. We notice that they are all released with open access. A limitation is only imposed by the CC-BY-NC license that does not permit commercial use of the resources. However, it is used only for a rather small percent of datasets (7%). Furthermore, despite the importance of specifying the type of license in order to improve shareability, a total of 41 linguistic resources in the original LOD Cloud and 70 resources in Annohub presented no values for the license of the data. The values for these licenses were manually enriched by using the information provided in the resource's metadata. This way values have been found for 104 datasets, with only 7 datasets without enough information on the website/documentation provided.

Table 4

Licenses that apply to more than one linguistics datasets and respective number of datasets.

Type	LOD Cloud	Annohub	Enriched
CC-BY	36	241	289 (+12)
GPL	0	191	214 (+23)
CC-BY-NC	4	0	45 (+41)
CC-BY-SA	25	25	70 (+20)
WordNet	9	0	13 (+4)
ODC-BY	4	0	5 (+1)
CC-zero	4	0	5 (+1)
SUC	0	0	2 (+2)
Others	13	3	16 (=)
N/A	41	70	7 (-104)
Total	136	530	666

6.3. LCRsubclass

In the LLOD cloud, resources are classified into the following types:

- *corpora* (defined as “collections of language data”),
- lexical-conceptual resources (“focus on the general meaning of words and the structure of semantic concepts”)
 - * *lexicons and dictionaries*,
 - * *terminologies, thesauri and knowledge bases*,
- metadata (“resources providing information about language and language resource”) [20].
 - * *linguistics resource metadata* (“linguistic resource metadata repositories, including bibliographical data”),
 - * *linguistic data categories* (“e.g., grammatical categories or language identifiers”),
 - * *typological databases* (“collections of features and inventories of individual languages, e.g., from linguistic typology”) [20].
- *other resources*.

All types written in italics in this classification are used in the LLOD Cloud for classifying resources and, in order to ensure consistency, we used the same set for assigning a type to those resources lacking one. We recall that, in the enriched metadata, types were assigned to every single dataset of the domain linguistics.

Table 5 shows the counts of linguistics resources per type, in the enriched metadata. It is clear that most resources of this domain fall either in the type of corpora or of lexicons & dictionaries. 65 out of the 315 cor-

pora are actually treebanks, almost all (except one) released within Universal Dependencies. When working with corpora, their levels of annotation represent important information, useful for, e.g., choosing one resource over another. In Annohub, the annotation model of the resources has been automatically inserted into the description.

Also, among the *Lexicons and Dictionaries* types, there are 42 wordnets, while ontologies are counted as *Terminologies, Thesauri and Knowledge Bases* type. Given the proven importance of such resources for NLP tasks, it could be important for a user to easily find and distinguish them from resources of the same type. At the moment, their name is the only way to distinguish them within the type they are assigned to. As it happens for the domains, in the future, types could benefit from a review.

Table 5

Number of linguistics datasets for each type, in the enriched metadata.

Type	Datasets
Corpora	315
Lexicons & Dictionaries	303
Terminologies, Thesauri & Knowledge Bases	30
Linguistic Data Categories	12
Linguistic Resource Metadata	4
Typological Databases	2
Total	666

The number of datasets for each language gives an overview on how languages are represented. A finer-grained perspective is given by looking at the types of resource available for each language. For this analysis, we focus on the 24 official languages of the European Union and present, in Table 6, not only the total number of linguistics datasets, but also the number of resources of the three most common types. For each of the previous, we show the total of resources including multilingual (All), counting once for each covered language, and also considering just monolingual datasets – i.e., dedicated exclusively to the target language (Mono). The latter is relevant because the coverage of different languages in some multilingual resources is significantly different. Moreover, they rarely focus on issues specific of one or a minority of languages.

We note an imbalanced distribution of the three types, first explained by the fact that there are much less datasets of the type *Terminologies, Thesauri & Knowledge Bases*, and when we look at monolingual

resources, only English (6), Finnish (YSA – *General Finnish Thesaurus*⁴³) and German (*Thesaurus Datenwissen*⁴⁴) have one resource of this type. Yet, even though the total number of Corpora and Lexicons & Dictionaries is close (315 and 303, see Table 5), all languages but Swedish have significantly more datasets of the latter than of the former type. One reason for this is the fact that there are much more multilingual Lexicons & Dictionaries, including bilingual (e.g., *Aper-tium*) and multilingual dictionaries (e.g., DBnary RDF editions of Wiktionary, some of which covering hundreds of languages). We recall that these multilingual resources are counted once for each language represented. When looking at monolingual datasets, we also note that there is no corpus exclusively dedicated to Lithuanian and Maltese, and no lexicons or dictionaries for nine languages (Czech, Estonian, Hungarian, Irish, Latvian, Lithuanian, Maltese, Slovenian, Spanish).

Apart from the EU languages, other well-represented languages in the enriched metadata, with at least 30 linguistic datasets, include two languages spoken in Spain, namely Catalan (43 datasets, two monolingual) and Galician (31, 4), as well as Russian (38, 2), Japanese (38, 4), Turkish (33, 2), Esperanto (33, 1, though not a single corpus) and Latin (31, 3).

6.4. Resource Accessibility

In this section we provide information about the accessibility of the dump, SPARQL endpoint, and the ontology for the linguistics LOD datasets. Datasets from Annohub are considered to be available as their availability was checked in Spring 2019.

One of the main concerns about the availability and accessibility of LOD datasets is the fact that they become unavailable in time, which is considered as the main threat to the success of the Semantic Web [32]. Even though LOD Cloud reports resource unavailability by means of an alert signal, this information is not always correct. We could find and download datasets for which LOD cloud assigned the alert and vice versa. For this reason, we checked the availability of all linguistics datasets manually.

There exist two ways to consume LLOD data; (i) download their data dump, and (ii) query them by their SPARQL endpoint. The SPARQL language is the stan-

⁴³<http://finto.fi/ysa/en/>

⁴⁴<http://thesaurus.datenwissen.de/>

Table 6

Linguistic resource types for each official EU language. ‘All’ includes multilingual resources and ‘Mono’ only resources exclusively dedicated to the target language.

Language	All Linguistics		Corpora		Lexicons & Dictionaries		Terminologies Thesauri & KBs	
	All	Mono	All	Mono	All	Mono	All	Mono
Bulgarian	33	2	3	1	30	1	0	0
Croatian	28	2	3	1	25	1	0	0
Czech	30	3	5	3	25	0	0	0
Danish	30	2	1	1	28	1	1	0
Dutch	43	3	5	2	36	1	2	0
English	146	38	18	9	108	15	13	6
Estonian	25	1	2	1	23	0	0	0
Finnish	42	4	2	2	38	1	2	1
French	66	4	7	2	55	2	4	0
German	66	8	7	4	54	3	5	1
Modern Greek	35	4	2	1	32	3	1	0
Hungarian	26	1	2	1	24	0	0	0
Irish	27	1	1	1	26	0	0	0
Italian	54	5	4	2	49	3	1	0
Latvian	24	1	1	1	23	0	0	0
Lithuanian	26	0	1	0	25	0	0	0
Maltese	22	0	0	0	22	0	0	0
Polish	47	2	3	1	44	1	0	0
Portuguese	48	4	4	3	43	1	1	0
Romanian	31	2	3	1	27	1	1	0
Slovak	27	2	3	1	24	1	0	0
Slovenian	28	2	3	2	25	0	0	0
Spanish	66	5	6	4	57	0	3	0
Swedish	283	216	230	211	48	1	2	0

dard query language proposed by the W3C⁴⁵ to query a collection of RDF triples [33]. Virtuoso [34] and Jena [35] are just two examples of triple stores that offer also a SPARQL interface. Users are able to query the triples on the Web because of the SPARQL protocol [36]: clients submit SPARQL queries through a specific `http` interface and the server executes these queries and responds with the results. Each client may submit unique and highly specific queries. This has as consequence requests timeout because of server overload. In such cases `http` caching mechanisms are ineffective as they can only optimize repeated identical queries. The architecture of SPARQL protocol demands the server to respond to highly complex requests, thus reliable public SPARQL endpoints are an exceptionally difficult challenge [37]. Such challenges contribute to the low availability of public SPARQL endpoints [38].

The other most trivial way to consume data is to access and download its dump. Data dump is a single-file that represent a part of or the entire dataset. It can contain some triples (e.g., `reuters-128-nif-ner-corpus`⁴⁶) up to billion triples (e.g., `dbpedia-abstract-corpus`⁴⁷). Because metadata about the data are often missing, consumers need to download the dump and make some exploratory queries. In such cases, consumers set up their own private SPARQL endpoint to host the data. However, as this resolves some issues, it has several drawbacks [37]: (i) setting up a SPARQL endpoint requires (possibly expensive) infrastructural support, (ii) involves (often manual) set-up and maintenance, (iii) the data are not up-to-date, and (iv) the entire dataset should be loaded in the server, even though just a part of it is needed.

⁴⁵<https://www.w3.org/>

⁴⁶<https://raw.githubusercontent.com/AKSW/n3-collection/master/Reuters-128.ttl>

⁴⁷<http://downloads.dbpedia.org/2015-04/ext/nlp/abstracts/en>

Table 7
Linguistic resource dump, SPARQL endpoint and ontology availability and accessibility.

			Original	Updated
Accessibility	downloadLocation (of dump)	URL	72	136 (+64)
		N/A	64	0 (-64)
		Total	136	136 (=)
	accessLocation (of SPARQL)	URL	N/A	71
		unknow	N/A	65
		Total	N/A	136
	externalResource	URL	N/A	40
		N/A	N/A	96
		Total	N/A	136
Quality	accessibleThroughQuery (endpoint availability)	yes	41	31 (-10)
		no	3	40 (+37)
		N/A	92	65 (-27)
		Total	136	136(=)
	distributionLocation/comment (dump availability)	yes	N/A	96
		no	N/A	40
		Total	N/A	136

Table 7 summarizes the accessibility and availability (which we consider under the quality criteria) information about linguistic datasets (updated column). We include in this table also the statistics about the accessibility and availability of LLOD considering only the information in their metadata (original column). The accessibility information is provided for the dump (downloadLocation), SPARQL endpoint (accessLocation) and ontology (externalResource). From the original metadata we were able to find the information (URL) for 72 datasets, while 64 do not provide any information. We checked and updated the information about the URL to the resource download for all 136 datasets. LLOD metadata do not provide any information about the access to the SPARQL endpoint or about the accessibility and availability of the ontology. However, we were able to find the URL of the SPARQL endpoint for 71 datasets, while there is no information for 65 datasets. Regarding the accessibility of the ontology, we could find such information for 40 datasets while we are missing it for 96.

The fact that datasets provide a link to the dump, endpoint of ontology does not mean that such information is actually available. Indeed, from 71 datasets that provide a link to the sparql endpoint only for 31 this link is actually working. Only on three datasets (emn, saldom-rdf and saldo-rdf) we were able to run only some specific example queries. The modelling of such datasets is out of the scope of this paper, thus we consider their sparql endpoint as available.

In the metadata of the original LOD we have the information about the status of their endpoint with values such as not available, available or empty. Within the metadata, 41 datasets provide the information about the SPARQL status as available, 3 as not available, while for most of them (92) this information is completely missing.

Only 21% of linguistics LOD datasets have a downloadable dump and an available SPARQL endpoint. The dump, SPARQL endpoint and ontology, is available only for 4 datasets (dbnary, premon, getty-aat, rkb-explorer-wordnet).

Even though LOD Cloud is considered a gold mine, its value is threatened by the unavailability of resources over time. As we can see from Table 7 only 70% of the linguistics datasets are available for download and only 30% of them are accessible through the SPARQL endpoint.

7. Conclusion and Future Work

In this paper, we present a preliminary investigation on linguistic LD resources and the metadata used to represent them within two repositories, namely the LOD Cloud and Annohub, with the aim of assessing the existing metadata and proposing their enrichment and alignment.

As first results, we notice that LOD datasets span through nine domains with the most represented being Life Sciences, while the linguistics domain comes only

in fourth place. With reference to languages we noticed several inconsistencies among various resources, e.g., in the way such information is registered and in the use of different or inconsistent labels. When considering only the linguistics domain, the number of distinct languages is very high.

Further analysing LD in the linguistic domain, we observe that most resources fall either in the type of corpora or of lexicons & dictionaries and that they usually present an open license.

Finally, with reference to the accessibility of the data, the dump is available only for 70% of linguistics LOD datasets. With regard to the SPARQL accessibility, only 30% have a working endpoint.

As consequence of this recognition, in order to satisfy the accessibility and usability principles for LD resources, we propose a new coherent and consistent metadata resource, aligned with a set of META-SHARE properties and classes, which encompasses enriched metadata from both repositories. Such an alignment could help quality assessment of resources and metadata, e.g., providing information about working accesses to those resources.

Future work includes a further metadata enrichment, with reference to the vocabularies and models applied in the development of such resources, together with a review of domains and types used to classify them.

Being aware that the manual enrichment is time-consuming, as for the metadata consistency check and the accessibility evaluation, we plan to implement a low-cost way to automatically achieve this task. One option is to further exploit the data already present in the database to fill in missing values. In fact, other fields in the original metadata repositories might be used as a source of additional information for data enrichment. The process of automatization of these tasks would also help with the creation and implementation of a tool to convert a non-conforming resource description to one conforming to the META-SHARE model. This tool would give users the possibility to share their own resources regardless of their consistency with a metadata model, thus greatly improving interoperability between linguistic datasets without the need for manual data refinement. We also consider to support the distributed and collaborative creation and extension of LLD by providing best practices to easily extend existing linguistic resources and publish their extensions as linked data.

Acknowledgments

This work has been carried out within the COST Action Nexus Linguarum CA 18209.

Maria Pia di Buono has been supported by Programma Operativo Nazionale Ricerca e Innovazione 2014-2020 - Fondo Sociale Europeo, Azione I.2 "Attrazione e Mobilità Internazionale dei Ricercatori" Avviso D.D. n 407 del 27/02/2018.

Blerina Spahiu has been supported by FOODNET project (<http://www.food-net.it/>)

References

- [1] N. Calzolari, N. Bel, K. Choukri, J. Mariani, M. Monachini, J. Odiijk, S. Piperidis, V. Quochi and C. Soria, Final FLReNet Deliverable: Language Resources for the Future-The Future of Language Resources, *The Strategic Language Resource Agenda. FLReNet project* (2011).
- [2] C. Chiarcos, P. Cimiano, T. Declerck and J.P. McCrae, Linguistic linked open data (lloD): introduction and overview, in: *Proceedings of the 2nd Workshop on Linked Data in Linguistics (LDL-2013): Representing and linking lexicons, terminologies and other language data*, 2013, p. i–xi.
- [3] J.P. McCrae, J. Bosque-Gil, J. Gracia, P. Buitelaar and P. Cimiano, The Ontolex-Lemon model: development and applications, in: *Proceedings of eLex 2017 conference*, 2017, pp. 19–21.
- [4] C. Bizer, T. Heath and T. Berners-Lee, Linked data: The story so far, in: *Semantic services, interoperability and web applications: emerging concepts*, IGI Global, 2011, pp. 205–227.
- [5] A. Assaf, A. Senart and R. Troncy, Roomba: automatic validation, correction and generation of dataset metadata, in: *Proceedings of the 24th International Conference on World Wide Web*, 2015, pp. 159–162.
- [6] R. Meusel, B. Spahiu, C. Bizer and H. Paulheim, Towards Automatic Topical Classification of LOD Datasets, in: *Proceedings of the Workshop on Linked Data on the Web, LDOW-co-located with the 24th International World Wide Web Conference, WWW 19 may*, Vol. 1409, 2015.
- [7] B. Spahiu, A. Maurino and R. Meusel, Topic profiling benchmarks in the linked open data cloud: Issues and lessons learned, *Semantic Web* **10**(2) (2019), 329–348.
- [8] F. Abromeit, C. Fäth and L. Glaser, Annohub–Annotation Metadata for Linked Data Applications, in: *Proceedings of the 7th Workshop on Linked Data in Linguistics (LDL-2020) @LREC2020*, 2020, pp. 36–44.
- [9] J. Bosque-Gil, J. Gracia, E. Montiel-Ponsoda and A. Gómez-Pérez, Models to represent linguistic linked data, *Natural Language Engineering* **24**(6) (2018), 811–859.
- [10] A. Hasnain, R. Fox, S. Decker and H.F. Deus, Cataloguing and linking life sciences LOD Cloud, in: *1st International Workshop on Ontology Engineering in a Data-driven World co-located with EKAW12*, 2012, pp. 114–130.
- [11] J. Debattista, C. Lange, S. Auer and D. Cortis, Evaluating the quality of the LOD cloud: An empirical investigation, *Semantic Web* **9**(6) (2018), 859–901.

- [12] J. Debattista, C. Lange and S. Auer, Representing Dataset Quality Metadata using Multi-Dimensional Views, 2014.
- [13] A. Zaveri, A. Rula, A. Maurino, R. Pietrobon, J. Lehmann and S. Auer, Quality assessment for Linked Data: A Survey, *Semantic Web* **7** (2015), 63–93. doi:10.3233/SW-150175.
- [14] A. Hogan, J. Umbrich, A. Harth, R. Cyganiak, A. Polleres and S. Decker, An empirical survey of Linked Data conformance, *Journal of Web Semantics* **14** (2012), 14–44, Special Issue on Dealing with the Messiness of the Web of Data. doi:<https://doi.org/10.1016/j.websem.2012.02.001>. <http://www.sciencedirect.com/science/article/pii/S1570826812000352>.
- [15] L. Ding and T. Finin, Characterizing the Semantic Web on the Web, 2006, pp. 242–257. ISBN 978-3-540-49029-6. doi:10.1007/11926078_18.
- [16] M.R. Kamdar and M.A. Musen, An Empirical Meta-analysis of the Life Sciences (Linked?) Open Data on the Web, 2020.
- [17] H. Paulheim, Knowledge graph refinement: A survey of approaches and evaluation methods, *Semantic Web* **8** (2017), 489–508.
- [18] M. Gavriliadou, P. Labropoulou, E. Desipri, S. Piperidis, H. Papageorgiou, M. Monachini, F. Frontini, T. Declerck, G. Francopoulo, V. Arranz, V. Mapelli and A. Ilsp, The META-SHARE Metadata Schema for the Description of Language Resources, 2012. doi:10.13140/2.1.4302.4644.
- [19] M. Schmachtenberg, C. Bizer and H. Paulheim, Adoption of the linked data best practices in different topical domains, in: *International Semantic Web Conference*, Springer, 2014, pp. 245–260.
- [20] J. McCrae, C. Chiarcos, F. Bond, P. Cimiano, T. Declerck, G. de Melo, J. Gracia, S. Hellmann, B. Klimek, S. Moran, P. Osenova, A. Pareja-Lora and J. Pool, The Open Linguistics Working Group: Developing the Linguistic Linked Open Data Cloud, 2016.
- [21] R. Albertoni, M. De Martino, S. Di Franco, V. De Santis and P. Plini, EARTH: an environmental application reference thesaurus in the linked open data cloud, *Semantic Web* **5**(2) (2014), 165–171.
- [22] J.P. McCrae and P. Cimiano, Linghub: a Linked Data based portal supporting the discovery of language resources., *SEMANTICS (Posters & Demos)* **1481** (2015), 88–91.
- [23] C. Chiarcos, B. Klimek, C. Fäth, T. Declerck and J.P. McCrae, On the Linguistic Linked Open Data Infrastructure, in: *Proceedings of the 1st International Workshop on Language Technology Platforms (IWLTP 2020)*, 2020, pp. 8–15.
- [24] J. Nivre, M.-C. De Marneffe, F. Ginter, Y. Goldberg, J. Hajic, C.D. Manning, R. McDonald, S. Petrov, S. Pyysalo, N. Silveira et al., Universal dependencies v1: A multilingual treebank collection, in: *Proceedings of the Tenth International Conference on Language Resources and Evaluation (LREC'16)*, 2016, pp. 1659–1666.
- [25] F. Giunchiglia, V. Maltese, F. Farazi and B. Dutta, GeoWordNet: a resource for geo-spatial applications, in: *Extended Semantic Web Conference*, Springer, 2010, pp. 121–136.
- [26] L.M. Schriml, E. Mittraka, J. Munro, B. Tauber, M. Schor, L. Nickle, V. Felix, L. Jeng, C. Bearer, R. Lichenstein et al., Human Disease Ontology 2018 update: classification, content and workflow expansion, *Nucleic acids research* **47**(D1) (2019), D955–D962.
- [27] P. Jaiswal, S. Avraham, K. Ilic, E.A. Kellogg, S. McCouch, A. Pujar, L. Reiser, S.Y. Rhee, M.M. Sachs, M. Schaeffer et al., Plant Ontology (PO): a controlled vocabulary of plant structures and growth stages, *Comparative and functional genomics* **6**(7–8) (2005), 388–397.
- [28] J. Sheridan and J. Tennison, Linking UK Government Data, in: *Proceedings of the WWW 2010 Workshop on Linked Data on the Web (LDOW)*, 2010.
- [29] R. Navigli and S.P. Ponzetto, BabelNet: The automatic construction, evaluation and application of a wide-coverage multilingual semantic network, *Artificial intelligence* **193** (2012), 217–250.
- [30] M.A. Sherif and A.-C. Ngonga Ngomo, Semantic Quran, *Semantic Web* **6**(4) (2015), 339–345.
- [31] F. Bond and R. Foster, Linking and extending an open multilingual wordnet, in: *Proceedings of the 51st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2013, pp. 1352–1362.
- [32] R. Verborgh, O. Hartig, B. De Meester, G. Haesendonck, L. De Vocht, M. Vander Sande, R. Cyganiak, P. Colpaert, E. Mannens and R. Van de Walle, Querying datasets on the web with high availability, in: *International Semantic Web Conference*, Springer, 2014, pp. 180–196.
- [33] S. Harris and A.S. Seaborne, 1.1 Query Language, W3C Recommendation 21 March 2013, 2013, URL: <http://www.w3.org/TR/sparql11-query/>. Accessed 14 (2013).
- [34] O. Erling and I. Mikhailov, Virtuoso: RDF support in a native RDBMS, in: *Semantic Web Information Management*, Springer, 2010, pp. 501–519.
- [35] M. Grobe, Rdf, jena, sparql and the 'semantic web', in: *Proceedings of the 37th annual ACM SIGUCCS fall conference: communication and collaboration*, 2009, pp. 131–138.
- [36] L. Feigenbaum, G.T. Williams, K.G. Clark and E. Torres, SPARQL 1.1 protocol, Recommendation, W3C (Mar. 2013), URL <http://www.w3.org/TR/sparql11-protocol>.
- [37] R. Verborgh, M. Vander Sande, P. Colpaert, S. Coppens, E. Mannens and R. Van de Walle, Web-Scale Querying through Linked Data Fragments., in: *LDOW*, Citeseer, 2014.
- [38] C. Buil-Aranda, A. Hogan, J. Umbrich and P.-Y. Vandenbussche, SPARQL web-querying infrastructure: Ready for action?, in: *International Semantic Web Conference*, Springer, 2013, pp. 277–293.
- [39] F. Manola, E. Miller, B. McBride et al., RDF primer, W3C recommendation **10**(1–107) (2004), 6.
- [40] D.L. McGuinness, F. Van Harmelen et al., OWL web ontology language overview, W3C recommendation **10**(10) (2004), 2004.
- [41] C. Chiarcos and A. Pareja-Lora, Open Data – Linked Data – Linked Open Data – Linguistic Linked Open Data (LLOD): A General Introduction, in: *Development of Linguistic Linked Open Data Resources for Collaborative Data-Intensive Research in the Language Sciences*, A. Pareja-Lora, M. Blume, B.C. Lust and C. Chiarcos, eds, The MIT Press, 2020.
- [42] T. Váradi, S. Krauwer, P. Wittenburg, M. Wynne and K. Koskenniemi, CLARIN: Common Language Resources and Technology Infrastructure, in: *Proceedings of the Sixth International Conference on Language Resources and Evaluation (LREC'08)*, European Language Resources Association (ELRA), Marrakech, Morocco, 2008. http://www.lrec-conf.org/proceedings/lrec2008/pdf/317_paper.pdf.

- [43] S. Krauwer and E. Hinrichs, The CLARIN research infrastructure: resources and tools for e-humanities scholars, in: *Proceedings of the Ninth International Conference on Language Resources and Evaluation (LREC-2014)*, European Language Resources Association (ELRA), 2014, pp. 1525–1531.
- [44] J. Domingue, D. Fensel and J.A. Hendler, *Handbook of semantic web technologies*, Springer Science & Business Media, 2011.
- [45] G. Rehm, M. Berger, E. Elsholz, S. Hegele, F. Kintzel, K. Marheinecke, S. Piperidis, M. Deligiannis, D. Galanis, K. Gkirtzou, P. Labropoulou, K. Bontcheva, D. Jones, I. Roberts, J. Hajič, J. Hamrlová, L. Kačena, K. Choukri, V. Arranz, A. Vasiljevs, O. Anvari, A. Lagzdinš, J. Melņika, G. Backfried, E. Dikici, M. Janosik, K. Prinz, C. Prinz, S. Stampler, D. Thomas-Aniola, J.M. Gómez-Pérez, A. Garcia Silva, C. Berrío, U. Germann, S. Renals and O. Klejch, European Language Grid: An Overview, in: *Proceedings of the 12th Language Resources and Evaluation Conference*, European Language Resources Association, Marseille, France, 2020, pp. 3366–3380. <https://www.aclweb.org/anthology/2020.lrec-1.413>.
- [46] A. Assaf, R. Troncy and A. Senart, What's up LOD Cloud?, in: *European Semantic Web Conference*, Springer, 2015, pp. 247–254.
- [47] C. Fellbaum, A semantic network of English: the mother of all WordNets, in: *EuroWordNet: A multilingual database with lexical semantic networks*, Springer, 1998, pp. 137–148.